

# Remington Barrel Kit Spec's

Kit Includes: Fully Finished SS Barrel, SS Barrel Nut, SS Recoil Lug and SS Nut Wrench

## SAFETY FIRST!

These kits are installed just like a Savage Barrel Change. The only difference is that you have to remove the factory Remington barrel first. There are several companies that make action wrench tools for the Remington actions. We recommend that you consult your local gunsmith for getting your factory barrel removed correctly and safely. Do Not attempt to change your rifle barrel without following all possible safety standards related to fire arms work and Gunsmithing. McRees Multi Services LLC and/or Mcree's Precision is not responsible for unsafe practices and any work that you choose to do instead of hiring a trained professional to do the work for you.

**Caliber:**            **300 WIN MAG**, SS, 24 inches, 10 Twist, 4grv, Proprietary Contour

Muzzle:                +/- .900 dia, 5/8 x 24 TPI, (+/- 4.8 # Barrel, nut and lug)

Chamber:             Match Grade – 1000yd Spec's, optimum Bullet Wt. 190 grains to 230 grains

**Caliber:**            **308 WINCHESTER**, SS, 22 inches, 10 Twist, 5grv, Proprietary Contour

Muzzle:                +/- .900 dia, 5/8 x 24 TPI, (+/- 4.2 # Barrel, nut and lug)

Chamber:             Match Grade – 1000yd Spec's, optimum Bullet Wt. 175 grains to 210 grains

**Caliber:**            **6.5 Creedmoor**, SS, 24 inches, 8 Twist, 5grv, Proprietary Contour

Muzzle:                +/- .900 dia, 5/8 x 24 TPI, (+/- 4.8 # Barrel, nut and lug)

Chamber:             Match Grade – 1000yd Spec's, optimum Bullet Wt. 123 grains to 147 grains

**Caliber:**            **6 Creedmoor**, SS, 24 inches, 7.5 Twist, 4grv, Proprietary Contour

Muzzle:                +/- .900 dia, 5/8 x 24 TPI, (+/- 4.8 # Barrel, nut and lug)

Chamber:             Match Grade – 1000yd Spec's, optimum Bullet Wt. 105 grains to 115 grains

**Caliber:**            **243 WINCHESTER**, SS, 24 inch, 7.5 Twist 4grv, Proprietary Contour

Muzzle:                +/- .900 dia, 5/8 x 24 TPI, (+/- 4.8 Barrel, nut and lug)

Chamber:             Match Grade – 1000yd Spec's, optimum Bullet Wt. 105 grains to 115 grains

## \*SAFETY FIRST\* \*SAFETY FIRST\* \*SAFETY FIRST\*

These kits are installed just like a Savage Barrel Change. The only difference is that you have to remove the factory Remington barrel first. There are several companies that make action wrench tools for the Remington actions. We recommend that you consult your local gunsmith for getting your factory barrel removed correctly and safely.

Do not attempt to change your rifle barrel without following all possible safety standards related to firearms work and Gunsmithing. McRees Multi Services LLC and/or Mcree's Precision is not responsible for unsafe practices and any work that you choose to do instead of hiring a trained professional to do the work for you. (2017-rev3)